

Pinnacle Series

CLAD PATIO DOOR - FRENCH INSWING

ELEVATIONS

SCALE: 1/8" = 1'-0"

Mas. Opng. Clad
Rough Opng.
Frame
Glass


2-7	5-0 13/16	7-6 5/8	7-11 15/16	9-0 7/16	10-0 7/16
2-7	5-0 13/16	7-6 5/8	7-11 15/16	9-0 7/16	10-0 7/16
2-6 1/4	5-0 1/16	7-5 7/8	7-11 3/16	8-11 11/16	9-11 11/16
20	20	20	11 1/2 - 20 - 11 1/2	14 - 20 - 14	20

6-8 6-8 6-7 1/2 63 7/8						
	2668	5068	7668	16-50-1668	20-50-2068	26-50-2668
6-10 7/8 6-10 7/8 6-10 3/8 66 3/4						
	26610	50610	76610	16-50-16610	20-50-20610	26-50-26610
7-11 7/8 7-11 7/8 7-11 3/8 79 3/4						
	2680	5080	7680			
8-11 7/8 8-11 7/8 8-11 3/8 91 3/4						
	2690	5090				
9-11 7/8 9-11 7/8 9-11 3/8 103 3/4						
	26100	50100				

NOTE:
THE ACTIVE PANEL (X) CAN BE PLACED IN ANY POSITION AND HINGED IN EITHER DIRECTION, LEFT (XL), OR RIGHT (XR). THE REMAINING PANEL(S) MUST BE IN A FIXED POSITION.

FOR DOORS WITH HANDICAP SILL, SUBTRACT 1 3/8" FROM FRAME & ROUGH OPENING HEIGHTS.

OTHER GRILLE PATTERNS



PRAIRIE PLAZA

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD


- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 13/32" TO FRAME HEIGHT

FOR CLAD WILLIAMSBURG

- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 1/4" TO FRAME HEIGHT

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT TO CALCULATE MASONRY OPENING

OTHER PANEL OPTIONS



1/2 LITE PANEL 3/4 LITE PANEL 1/2 LITE DIVIDED PANEL 3/4 LITE DIVIDED PANEL

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING
ALL UNITS LISTED ARE BUILT AS ONE FRAME

Pinnacle Series

CLAD PATIO DOOR - FRENCH INSWING

ELEVATIONS

SCALE: 1/8" = 1'-0"

Mas. Opng. Clad
Rough Opng.
Frame
Glass

2-9	5-4 13/16	8-0 5/8	7-11 15/16
2-9	5-4 13/16	8-0 5/8	7-11 15/16
2-8 1/4	5-4 1/16	7-11 7/8	7-11 3/16
22	22	22	9 1/2 - 22 - 9 1/2

6-8 6-8 6-7 1/2 63 7/8				
	2868	5468	8068	14-54-1468

6-10 7/8 6-10 7/8 6-10 3/8 66 3/4				
	28610	54610	80610	14-54-14610

7-11 7/8 7-11 7/8 7-11 3/8 79 3/4			
	2880	5480	8080

8-11 7/8 8-11 7/8 8-11 3/8 91 3/4		
	2890	5490

9-11 7/8 9-11 7/8 9-11 3/8 103 3/4		
	28100	54100

NOTE:
THE ACTIVE PANEL (X) CAN BE PLACED IN ANY POSITION AND HINGED IN EITHER DIRECTION, LEFT (XL), OR RIGHT (XR). THE REMAINING PANEL(S) MUST BE IN A FIXED POSITION.

FOR DOORS WITH HANDICAP SILL, SUBTRACT 1 3/8" FROM FRAME & ROUGH OPENING HEIGHTS.

OTHER GRILLE PATTERNS

PRAIRIE	PLAZA

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD

- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 13/32" TO FRAME HEIGHT

FOR CLAD WILLIAMSBURG

- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 1/4" TO FRAME HEIGHT

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT TO CALCULATE MASONRY OPENING

OTHER PANEL OPTIONS

1/2 LITE PANEL	3/4 LITE PANEL	1/2 LITE DIVIDED PANEL	3/4 LITE DIVIDED PANEL

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING
ALL UNITS LISTED ARE BUILT AS ONE FRAME

Pinnacle Series

CLAD PATIO DOOR - FRENCH INSWING

ELEVATIONS

SCALE: 1/8" = 1'-0"


Mas. Opp. Clad
Rough Opp.
Frame
Glass

	3-1	6-0 13/16	9-0 5/8	8-11 15/16	10-0 7/16
	3-1	6-0 13/16	9-0 5/8	8-11 15/16	10-0 7/16
	3-0 1/4	6-0 1/16	8-11 7/8	8-11 3/16	9-11 11/16
	26	26	26	11 1/2 - 26 - 11 1/2	14 - 26 - 14
6-8					
6-8	3068	6068	9068	16-60-1668	20-60-2068
6-7 1/2					
6-8 7/8	30610	60610	90610	16-60-16610	20-60-20610
6-10 7/8					
6-10 7/8	3080	6080	9080		
6-10 3/8					
66 3/4	3090	6090			
7-11 7/8					
7-11 7/8	30100	60100			
7-11 3/8					
79 3/4					
8-11 7/8					
8-11 7/8					
8-11 3/8					
91 3/4					
9-11 7/8					
9-11 7/8					
9-11 3/8					
103 3/4					

NOTE:
THE ACTIVE PANEL (X) CAN BE PLACED IN ANY POSITION AND HINGED IN EITHER DIRECTION, LEFT (XL), OR RIGHT (XR). THE REMAINING PANEL(S) MUST BE IN A FIXED POSITION.

FOR DOORS WITH HANDICAP SILL, SUBTRACT 1 3/8" FROM FRAME & ROUGH OPENING HEIGHTS.

OTHER GRILLE PATTERNS



PRAIRIE PLAZA

UNIT SIZE INFORMATION


FOR CLAD BRICKMOULD

- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 13/32" TO FRAME HEIGHT

FOR CLAD WILLIAMSBURG

- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 1/4" TO FRAME HEIGHT

OTHER PANEL OPTIONS



1/2 LITE PANEL 3/4 LITE PANEL 1/2 LITE DIVIDED PANEL 3/4 LITE DIVIDED PANEL

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT TO CALCULATE MASONRY OPENING

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING
ALL UNITS LISTED ARE BUILT AS ONE FRAME

Pinnacle Series

CLAD PATIO DOOR - FRENCH INSWING

ELEVATIONS


SCALE: 1/8" = 1'-0"

Mas. Opp. Clad
 Rough Opp.
 Frame
 Glass


11-0 7/16
 11-0 7/16
 10-11 11/16
 20 - 26 - 20

12-0 7/16
 12-0 7/16
 11-11 11/16
 26

6-8
 6-8
 6-7 1/2
 6-7 1/2




26-60-2668




30-60-3068

6-10 7/8
 6-10 7/8
 6-10 3/8
 6-10 3/8



26-60-26610



30-60-30610

Pinnacle Series
















CLAD PATIO DOOR - FRENCH INSWING

ELEVATIONS


SCALE: 1/8" = 1'-0"

Mas. Opg. Clad
Rough Opg.
Frame
Glass


3-2 1/2	6-3 13/16	4-0 3/4
3-2 1/2	6-3 13/16	4-0 3/4
3-1 3/4	6-3 1/16	4-0
27 1/2	27 1/2	14

6-8 6-8 6-7 1/2 63 7/8	 3268	 6468	 4068 BI-HINGE ONLY
6-10 7/8 6-10 7/8 6-10 3/8 66 3/4	 32610	 64610	 40610 BI-HINGE ONLY
7-11 7/8 7-11 7/8 7-11 3/8 79 3/4	 3280	 6480	 4080 BI-HINGE ONLY
8-11 7/8 8-11 7/8 8-11 3/8 91 3/4	 3290	 6490	 4090 BI-HINGE ONLY
9-11 7/8 9-11 7/8 9-11 3/8 103 3/4	 32100	 64100	 40100 BI-HINGE ONLY

OTHER GRILLE PATTERNS



OTHER PANEL OPTIONS



NOTE:
THE ACTIVE PANEL (X) CAN BE PLACED IN ANY POSITION AND HINGED IN EITHER DIRECTION, LEFT (XL), OR RIGHT (XR). THE REMAINING PANEL(S) MUST BE IN A FIXED POSITION.

FOR DOORS WITH HANDICAP SILL, SUBTRACT 1 3/8" FROM FRAME & ROUGH OPENING HEIGHTS.

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD

- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 13/32" TO FRAME HEIGHT

FOR CLAD WILLIAMSBURG

- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 1/4" TO FRAME HEIGHT

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING
ALL UNITS LISTED ARE BUILT AS ONE FRAME

Pinnacle Series

CLAD PATIO DOOR - FRENCH INSWING SIDELITES

ELEVATIONS

SCALE: 1/8" = 1'-0"

	1-3	1-5	1-7	2-1 1/4
Mas. Oppg. Clad	1-3	1-5	1-7	2-1 1/4
Rough Oppg.	1-2	1-4	1-6	2-0 1/4
Frame	7 1/2	9 1/2	11 1/2	14
Glass				
6-8				
6-8				
6-7 1/2				
63 7/8	1268	1468	1668	2068
6-11				
6-11				
6-10 1/2				
66 3/4	12610	14610	16610	20610
8-0				
8-0				
7-11 3/8				
79 3/4	1280	1480	1680	2080
9-0				
9-0				
8-11 3/8				
91 3/4	1290	1490	1690	2090


NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING

Pinnacle Series

CLAD PATIO DOOR - FRENCH INSWING


HANDING CONFIGURATIONS (ALL HANDINGS ARE VIEWED FROM THE EXTERIOR)

SINGLE DOOR




XR O XL

THREE UNIT DOOR




XR-O-O O-O-XL


DOUBLE UNIT DOOR




XR-O O-XL



XL-O-O O-O-XR




XL-O O-XR




O-XR-O O-XL-O


BI-HINGE DOOR



XO OR OX




O-XO OR O-OX




XO-O OR OX-O


FOUR UNIT DOOR



O-O-XR-O



O-XL-O-O



O-XO-O OR O-OX-O


FLANKER UNITS MUST BE STATIONARY FOR QUAD HANDINGS

Pinnacle Series


CLAD PATIO DOOR - FRENCH INSWING

SCREEN OPTIONS


SWINGING SCREEN OPTION




XR *



XO *




XL *




OX *

SLIDING SCREEN OPTION




X-O +




O-X +


NO SCREEN AVAILABLE (IF ORDERED AS ONE FRAME)




O-XO +




XO-O +




X-O-O +




O-O-X +




O-X-O +




O-XO-O +



O-O-X-O +



O-X-O-O +



O-XO-O +

* Swing screens will also work on these configurations if they are mullied to other units

+ Standard handing configurations as shown are continuous head and sill. Swing screens can be applied on these units if operating doors are ordered separately and mullied to the stationary doors.

Pinnacle Series

CLAD INSWING PATIO DOOR - IN-SASH TRANSOMS

ELEVATIONS

SCALE: 1/8" = 1'-0"

Mas. Opg. Clad Rough Opg. Frame Glass	2-7	5-0 13/16	5-0 13/16	7-6 5/8	7-6 5/8
	2-7	5-0 13/16	5-0 13/16	7-6 5/8	7-6 5/8
	2-6 1/4	5-0 1/16	5-0 1/16	7-5 7/8	7-5 7/8
	20	49 13/16	20	20	79 5/8
1-4 1/2					
1-4 1/2	2611	5011	5011-2	7611-3	
1-4 1/2					
1-4 1/2	2614	5014	5014-2	7614-3	7614
2-0 1/2					
2-0 1/2	2620	5020	5020-2	7620-3	7620
Mas. Opg. Clad Rough Opg. Frame Glass	2-9	5-4 13/16	5-4 13/16	8-0 5/8	8-0 5/8
	2-9	5-4 13/16	5-4 13/16	8-0 5/8	8-0 5/8
	2-8 1/4	5-4 1/16	5-4 1/16	7-11 7/8	7-11 7/8
	22	53 13/16	22	22	85 5/8
1-4 1/2					
1-4 1/2	2811	5411	5411-2	8011-3	
1-4 1/2					
1-4 1/2	2814	5414	5414-2	8014-3	8014
2-0 1/2					
2-0 1/2	2820	5420	5420-2	8020-3	8020
Mas. Opg. Clad Rough Opg. Frame Glass	3-1	6-0 13/16	6-0 13/16	9-0 5/8	9-0 5/8
	3-1	6-0 13/16	6-0 13/16	9-0 5/8	9-0 5/8
	3-0 1/4	6-0 1/16	6-0 1/16	8-11 7/8	8-11 7/8
	26	61 13/16	26	26	97 5/8
1-4 1/2					
1-4 1/2	3011	6011	6011-2	9011-3	
1-4 1/2					
1-4 1/2	3014	6014	6014-2	9014-3	9014
2-0 1/2					
2-0 1/2	3020	6020	6020-2	9020-3	9020
Mas. Opg. Clad Rough Opg. Frame Glass	3-2 1/2	6-3 13/16	6-3 13/16		
	3-2 1/2	6-3 13/16	6-3 13/16		
	3-1 3/4	6-3 1/16	6-3 1/16		
	28	65 13/16	28		
1-4 1/2					
1-4 1/2	3211	6411	6411-2		
1-4 1/2					
1-4 1/2	3214	6414	6414-2		
2-0 1/2					
2-0 1/2	3220	6420	6420-2		

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD

- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 13/32" TO FRAME HEIGHT

FOR CLAD WILLIAMSBURG

- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 1/4" TO FRAME HEIGHT

NOTE:

ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT TO CALCULATE MASONRY OPENING

NOTES:

CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING


Pinnacle Series

CLAD PATIO DOOR - FRENCH INSWING


GRILLE PANELS FOR PANEL DOORS

SCALE: 1/8" = 1'-0"

3/4 LITE



PANEL HEIGHT & MIDRAIL LOCATIONS



NOTES:

HORIZONTAL GRILLE BARS WILL ONLY ALIGN WITH SIMILAR PANELS OR SIDE PANELS


Pinnacle Series

CLAD PATIO DOOR - FRENCH INSWING


GRILLE PANELS FOR PANEL DOORS

SCALE: 1/8" = 1'-0"

1/2 LITE



PANEL HEIGHT & MIDRAIL LOCATIONS



NOTES:
HORIZONTAL GRILLE BARS WILL ONLY ALIGN WITH SIMILAR PANELS OR SIDE PANELS

Pinnacle Series

CLAD PATIO DOOR - FRENCH OUTSWING

ELEVATIONS

SCALE: 1/8" = 1'-0"

Mas. Opng. Clad
Rough Opng.
Frame
Glass


2-7	5-0 13/16	7-6 5/8	8-0 1/16	9-0 9/16	10-0 9/16
2-7	5-0 13/16	7-6 5/8	8-0 1/16	9-0 9/16	10-0 9/16
2-6 1/4	5-0 1/16	7-5 7/8	7-11 5/16	8-11 13/16	9-11 13/16
20	20	20	11 1/2 - 20 - 11 1/2	14 - 20 - 14	20

6-7 1/2 6-7 1/2 6-7 63 7/8						
2668	5068	7668	16-50-1668	20-50-2068	26-50-2668	
6-10 3/8 6-10 3/8 6-9 7/8 66 3/4						
26610	50610	76610	16-50-16610	20-50-20610	26-50-26610	
7-11 3/8 7-11 3/8 7-10 7/8 79 3/4						
2680	5080	7680				
8-11 3/8 8-11 3/8 8-10 7/8 91 3/4						
2690	5090					
9-11 3/8 9-11 3/8 9-10 7/8 103 3/4						
26100	50100					

NOTE:
THE ACTIVE PANEL (X) CAN BE PLACED IN ANY POSITION AND HINGED IN EITHER DIRECTION, LEFT (XL), OR RIGHT (XR). THE REMAINING PANEL(S) MUST BE IN A FIXED POSITION.

FOR DOORS WITH HANDICAP SILL, SUBTRACT 7/8" FROM FRAME & ROUGH OPENING HEIGHTS.

OTHER GRILLE PATTERNS



UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD


- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 13/32" TO FRAME HEIGHT

FOR CLAD WILLIAMSBURG

- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 1/4" TO FRAME HEIGHT

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT TO CALCULATE MASONRY OPENING

OTHER PANEL OPTIONS
















NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING
ALL UNITS LISTED ARE BUILT AS ONE FRAME

Pinnacle Series

CLAD PATIO DOOR - FRENCH OUTSWING

ELEVATIONS


SCALE: 1/8" = 1'-0"

Mas. Opng. Clad Rough Opng. Frame Glass	2-9	5-4 13/16	8-0 5/8
6-7 1/2	2-9	5-4 13/16	8-0 5/8
6-7 1/2	2-8 1/4	5-4 1/16	7-11 7/8
6-7	22	22	22
63 7/8			
	2868	5468	8068
6-10 3/8			
6-10 3/8	28610	54610	80610
6-9 7/8			
66 3/4			
7-11 3/8			
7-11 3/8	2880	5480	8080
7-10 7/8			
79 3/4			
8-11 3/8			
8-11 3/8	2890	5490	
8-10 7/8			
91 3/4			
9-11 3/8			
9-11 3/8	28100	54100	
9-10 7/8			
103 3/4			

NOTE:
THE ACTIVE PANEL (X) CAN BE PLACED IN ANY POSITION AND HINGED IN EITHER DIRECTION, LEFT (XL), OR RIGHT (XR). THE REMAINING PANEL(S) MUST BE IN A FIXED POSITION.

FOR DOORS WITH HANDICAP SILL, SUBTRACT 7/8" FROM FRAME & ROUGH OPENING HEIGHTS.

OTHER GRILLE PATTERNS



PRARIE


PLAZA

UNIT SIZE INFORMATION

- FOR CLAD BRICKMOULD**
- ADD 2 13/16" TO FRAME WIDTH
 - ADD 1 13/32" TO FRAME HEIGHT
- FOR CLAD WILLIAMSBURG**
- ADD 6 1/2" TO FRAME WIDTH
 - ADD 3 1/4" TO FRAME HEIGHT

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT TO CALCULATE MASONRY OPENING

OTHER PANEL OPTIONS



1/2 LITE PANEL

3/4 LITE PANEL

1/2 LITE DIVIDED PANEL

3/4 LITE DIVIDED PANEL

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING
ALL UNITS LISTED ARE BUILT AS ONE FRAME

Pinnacle Series

CLAD PATIO DOOR - FRENCH OUTSWING

ELEVATIONS

SCALE: 1/8" = 1'-0"


Mas. Opg. Clad
Rough Opg.
Frame
Glass

	3-1	6-0 13/16	9-0 5/8	9-0 1/16	10-0 9/16
	3-1	6-0 13/16	9-0 5/8	9-0 1/16	10-0 9/16
	3-0 1/4	6-0 1/16	8-11 7/8	8-11 5/16	9-11 13/16
	26	26	26	11 1/2 - 26 - 11 1/2	14 - 26 - 14
6-7 1/2					
6-7 1/2	3068	6068	9068	16-60-1668	20-60-2068
6-7					
6-10 3/8	30610	60610	90610	16-60-16610	20-60-20610
6-9 7/8					
66 3/4	3080	6080	9080		
7-11 3/8					
7-11 3/8	3090	6090			
7-10 7/8					
79 3/4	30100	60100			
8-11 3/8					
8-11 3/8	3090	6090			
8-10 7/8					
91 3/4	30100	60100			
9-11 3/8					
9-11 3/8	30100	60100			
9-10 7/8					
103 3/4	30100	60100			


NOTE:
THE ACTIVE PANEL (X) CAN BE PLACED IN ANY POSITION AND HINGED IN EITHER DIRECTION, LEFT (XL), OR RIGHT (XR). THE REMAINING PANEL(S) MUST BE IN A FIXED POSITION.

FOR DOORS WITH HANDICAP SILL, SUBTRACT 7/8" FROM FRAME & ROUGH OPENING HEIGHTS.

OTHER GRILLE PATTERNS



OTHER PANEL OPTIONS



UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD

- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 13/32" TO FRAME HEIGHT

FOR CLAD WILLIAMSBURG

- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 1/4" TO FRAME HEIGHT

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT TO CALCULATE MASONRY OPENING

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING
ALL UNITS LISTED ARE BUILT AS ONE FRAME

Pinnacle Series

CLAD PATIO DOOR - FRENCH OUTSWING

ELEVATIONS

SCALE: 1/8" = 1'-0"

Mas. Opq. Clad
Rough Opq.
Frame
Glass

11-0 9/16

12-0 9/16

11-0 9/16

12-0 9/16


10-11 13/16

11-11 13/16


20 - 26 - 20

26

6-7 1/2
6-7 1/2
6-7
63 7/8




26-60-3068




30-30-3068

6-10 3/8
6-10 3/8
6-9 7/8
66 3/4



26-60-30610



30-60-30610

Pinnacle Series
















CLAD PATIO DOOR - FRENCH OUTSWING

ELEVATIONS


SCALE: 1/8" = 1'-0"

Mas. Opng. Clad
Rough Opng.
Frame
Glass


3-2 1/2	6-3 13/16	4-0 9/16
3-2 1/2	6-3 13/16	4-0 9/16
3-1 3/4	6-3 1/16	4-0 1/16
27 1/2	27 1/2	14

6-7 1/2 6-7 1/2 6-7 63 7/8	 3268	 6468	 4068 BI-HINGE ONLY
6-10 3/8 6-10 3/8 6-9 7/8 66 3/4	 32610	 64610	 40610 BI-HINGE ONLY
7-11 3/8 7-11 3/8 7-10 7/8 79 3/4	 3280	 6480	 4080 BI-HINGE ONLY
8-11 3/8 8-11 3/8 8-10 7/8 91 3/4	 3290	 6490	 4090 BI-HINGE ONLY
8-11 3/8 8-11 3/8 8-10 7/8 91 3/4	 32100	 64100	 40100 BI-HINGE ONLY

OTHER GRILLE PATTERNS



OTHER PANEL OPTIONS



NOTE:
THE ACTIVE PANEL (X) CAN BE PLACED IN ANY POSITION AND HINGED IN EITHER DIRECTION, LEFT (XL), OR RIGHT (XR). THE REMAINING PANEL(S) MUST BE IN A FIXED POSITION.

FOR DOORS WITH HANDICAP SILL, SUBTRACT 7/8" FROM FRAME & ROUGH OPENING HEIGHTS.

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD

- ▣ ADD 2 13/16" TO FRAME WIDTH
- ▣ ADD 1 13/32" TO FRAME HEIGHT

FOR CLAD WILLIAMSBURG

- ▣ ADD 6 1/2" TO FRAME WIDTH
- ▣ ADD 3 1/4" TO FRAME HEIGHT

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT TO CALCULATE MASONRY OPENING

















NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING
ALL UNITS LISTED ARE BUILT AS ONE FRAME

Pinnacle Series

CLAD PATIO DOOR - FRENCH OUTSWING SIDELITES

ELEVATIONS

SCALE: 1/8" = 1'-0"

	1-3	1-5	1-7	2-1 1/4
Mas. Opp. Clad	1-3	1-5	1-7	2-1 1/4
Rough Opg.	1-2	1-4	1-6	2-0 1/4
Frame	7 1/2	9 1/2	11 1/2	14
Class				
6-7 1/2				
6-7 1/2	1268	1468	1668	2068
6-7				
63 7/8				
6-10 1/2				
6-10 1/2	12610	14610	16610	20610
6-9 7/8				
66 3/4				
7-11 1/2				
7-11 1/2	1280	1480	1680	2080
7-10 7/8				
79 3/4				
8-11 1/2				
8-11 1/2	1290	1490	1690	2090
8-10 7/8				
91 3/4				

NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING

Pinnacle Series

CLAD PATIO DOOR - FRENCH OUTSWING

ELEVATIONS

SCALE: 1/8" = 1'-0"

Mass. Opq. Clad
Rough Opq.
Frame
Glass

3-2 1/2
3-2 1/2
3-1 3/4
27 1/2

6-2 3/4
6-2 3/4
6-2
27 1/2


Mass. Opq. Clad
Rough Opq.
Frame
Glass

6-2 3/4
6-2 3/4
6-2
63 3/4


6-2 3/4
6-2 3/4
6-2
27 1/2

DOORS

6-6 5/8
6-6 5/8
6-6 1/8
63 7/8




3268-A




6468-A

6-9 1/2
6-9 1/2
6-9
66 3/4




32610-A




64610-A

7-10 1/2
7-10 1/2
7-10
79 3/4




3280-A




6480-A

8-10 1/2
8-10 1/2
8-10
91 3/4




3290-A




6490-A

9-10 1/2
9-10 1/2
9-10
103 3/4



32100-A



64100-A

IN-SASH TRANSOMS

1-1 1/2
1-1 1/2
1-1
6 1/2




6411-A




6411-2-A

1-4 1/2
1-4 1/2
1-4
9 1/2




6414-A




6414-2-A

2-0 1/2
2-0 1/2
2-0
17 1/2




6420-A




6420-2-A

OTHER GRILLE PATTERNS




PRAIRIE




PLAZA


OTHER PANEL OPTIONS




1/2 LITE
PANEL



3/4 LITE
PANEL



1/2 LITE
DIVIDED PANEL



3/4 LITE
DIVIDED PANEL

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD

- ▣ ADD 2 13/16" TO FRAME WIDTH
- ▣ ADD 1 13/32" TO FRAME HEIGHT

FOR CLAD WILLIAMSBURG

- ▣ ADD 6 1/2" TO FRAME WIDTH
- ▣ ADD 3 1/4" TO FRAME HEIGHT

NOTE:

ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING

NOTES:

- ADA DOORS INCLUDE / REQUIRE 10" BOTTOM RAIL, 3-2 PANEL & HANDICAP SILL
- ADA DOORS ARE NOT RATED
- ADA DOORS COME WITH NO BORE & NO HARDWARE
- BI-HINGE DOORS DO NOT HAVE AN ASTRAGAL


CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING
ALL UNITS LISTED ARE BUILT AS ONE FRAME

Pinnacle Series


CLAD PATIO DOOR - FRENCH OUTSWING

HANDING CONFIGURATIONS (ALL HANDINGS ARE VIEWED FROM THE EXTERIOR)





SINGLE DOOR





THREE UNIT DOOR






DOUBLE UNIT DOOR



BI-HINGE DOOR



FOUR UNIT DOOR



FLANKER UNITS MUST BE STATIONARY FOR QUAD HANDINGS

Pinnacle Series

CLAD OUTSWING PATIO DOOR - IN-SASH TRANSOMS

ELEVATIONS

SCALE: 1/8" = 1'-0"

Mas. Opg. Clad Rough Opg. Frame Glass	2-7	5-0 13/16	5-0 13/16	7-6 5/8	7-6 5/8
	2-7	5-0 13/16	5-0 13/16	7-6 5/8	7-6 5/8
	2-6 1/4	5-0 1/16	5-0 1/16	7-5 7/8	7-5 7/8
	20	49 13/16	20	20	79 5/8
1-1 1/2					
1-4 1/2					
2-0 1/2					
2-0 1/2	2-9	5-4 13/16	5-4 13/16	8-0 5/8	8-0 5/8
2-9	5-4 13/16	5-4 13/16	8-0 5/8	8-0 5/8	
2-8 1/4	5-4 1/16	5-4 1/16	7-11 7/8	7-11 7/8	
22	53 13/16	22	22	85 5/8	
1-1 1/2					
1-4 1/2					
2-0 1/2					
2-0 1/2	3-1	6-0 13/16	6-0 13/16	9-0 5/8	9-0 5/8
3-1	6-0 13/16	6-0 13/16	9-0 5/8	9-0 5/8	
3-0 1/4	6-0 1/16	6-0 1/16	8-11 7/8	8-11 7/8	
26	61 13/16	26	26	97 5/8	
1-1 1/2					
1-4 1/2					
2-0 1/2					
3-2 1/2	3-2 1/2	6-3 13/16	6-3 13/16		
3-2 1/2	6-3 13/16	6-3 13/16	6-3 13/16		
3-1 3/4	6-3 1/16	6-3 1/16			
28	65 13/16	28			
1-1 1/2					
1-4 1/2					
2-0 1/2					

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD

- ▣ ADD 2 13/16" TO FRAME WIDTH
- ▣ ADD 1 13/32" TO FRAME HEIGHT

FOR CLAD WILLIAMSBURG

- ▣ ADD 6 1/2" TO FRAME WIDTH
- ▣ ADD 3 1/4" TO FRAME HEIGHT

NOTE:

ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT TO CALCULATE MASONRY OPENING

NOTES:

CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING


Pinnacle Series

CLAD PATIO DOOR - FRENCH OUTSWING


GRILLE PANELS FOR PANEL DOORS

SCALE: 1/8" = 1'-0"

3/4 LITE



PANEL HEIGHT & MIDRAIL LOCATIONS



NOTES:
HORIZONTAL GRILLE BARS WILL ONLY ALIGN WITH SIMILAR PANELS OR SIDE PANELS


Pinnacle Series

CLAD PATIO DOOR - FRENCH OUTSWING


GRILLE PANELS FOR PANEL DOORS

SCALE: 1/8" = 1'-0"

1/2 LITE



PANEL HEIGHT & MIDRAIL LOCATIONS



NOTES:
HORIZONTAL GRILLE BARS WILL ONLY ALIGN WITH SIMILAR PANELS OR SIDE PANELS